


## Clean-Room PU C-TL1813P

PRODUCT		DIMENSIONS	C-TL1813P
		Seat depth from lumbar support	410 mm
		Seat depth	430 mm
		Seat width	470 mm
		Backrest height from seat	350-420 mm
		Backrest height adjustment	70 mm
		Backrest width	420 mm
		Seat height	430-560 mm
TECHNICAL DESCRIPTION			
Seat	Internal structure in multilayered beech wood anatomically shaped, 11 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of soft integral polyurethane (PU-Soft). Colour Black BLK. Non-toxic material and without CFC/HCFC.		
Backrest	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs, covered by a compound of soft integral polyurethane (PU-Soft). Colour Black BLK. Non-toxic material and without CFC/HCFC.		
Mechanism	<b>AS3:</b> A-SYNCHRON TRI-LEVER, backrest inclination of 12° positive and 28° negative, seat of 5° positive and 3° negative, lockable in all positions. With combined activation of tilting mechanism and backrest inclination. Knob activated backrest height adjustment. According to UNI EN 1335-3.		
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.		
Base	<b>0901C:</b> 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.		
Castors	<b>0302:</b> hard castors (Ø 50 mm) in black nylon, self-braking.		
ACCESSORIES			
0860N	Height adjustable armrests. Supporting structure in steel with top in nylon. Black finish.		
M-0311	Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of 0302 castors.		
M-0351	Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.		
TEST			
UNI EN 1335-2+3			
ANSI/BIFMA X5.1/8			
ANSI/BIFMA X5.1/11			