


Clean-Room ESD PU Intense-Use C-TL1862HAP / C-TL1872HAP

PRODUCT		DIMENSIONS	C-TL1862HAP	C-TL1872HAP
		Seat depth from lumbar support	380 mm	380 mm
		Seat depth	430 mm	430 mm
		Seat width	470 mm	470 mm
		Backrest height from seat	350-420 mm	350-420 mm
		Backrest height adjustment	70 mm	70 mm
		Backrest width	420 mm	420 mm
		Seat height	510-710 mm	610-860 mm
		TECHNICAL DESCRIPTION		
Seat	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs and steel bars, covered by a compound of soft integral polyurethane mixed with carbon fibers (PU-Soft ESD). Colour Black BLK-ESD. Non-toxic and without CFC/HCFC. ESD material conductivity of 10 ⁷ ohm.			
Backrest	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs and steel bars, covered by a compound of soft integral polyurethane mixed with carbon fibers (PU-Soft ESD). Colour Black BLK-ESD. Non-toxic and without CFC/HCFC. ESD material conductivity of 10 ⁷ ohm.			
Mechanism	AS2: A-SYNCHRON BI-LEVER, independent backrest inclination of 9° positive and 16° negative, seat of 6° positive and 4° negative, lockable in all positions. Push button activated backrest height adjustment. According to UNI EN 1335-3.			
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), chrome finish. Class 4 according to DIN 4550.			
Base	0901C: 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.			
Glides	0331: conductive glides in black nylon (h 32 mm / Ø 50 mm).			
ACCESSORIES				
0860AN	Height adjustable conductive armrests. Supporting structure in steel with top in conductive nylon. Black finish.			
M-0321	Conductive castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.			
0700ESD	Conductive circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.			
NO-OIL	Gas lift with sealing ring for oil and grease.			
TEST				
UNI EN 1335-2+3				
EN 100015-1				
IEC 61340-5-1				