


## Clean-Room ESD Professional C-EX1111AS

PRODUCT	DIMENSIONS	A-EX1111AS	
	Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	440 mm 470 mm 510 mm 530-590 mm 60 mm 470 mm 420-550 mm	

### TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm variable thickness. Low formaldehyde emission according to class E1. Outer shell in recyclable techno-polymer for internal components protection. Additional shell in recyclable techno-polymer for mechanism total encasement and protection.
Backrest	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs. Outer shell in antistatic ESD recyclable techno-polymer for internal components protection.
Padding	Seat in PU-Flex, 45 mm thickness and 40 g/L density. Backrest in PU-Flex, 35 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.
Upholstery	<b>ECR7</b> Composition: 90% PVC, 10% cotton/polyester Weight: 630 g/m <sup>2</sup> Colour fastness to light: UNI EN ISO 105-B02 Xenotest (Level 5) Colours: Black 1104
Mechanism	<b>PCX</b> : PERMANENT CONTACT X, backrest inclination of 25°, lockable in all positions, with antishock. Up&Down activated backrest height adjustment, lockable in 7 positions. According to UNI EN 1335-3.
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), chrome finish. Class 4 according to DIN 4550.
Base	<b>0903C</b> : 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Castors	<b>0321</b> : conductive castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking.

### ACCESSORIES

0860AN	Height adjustable conductive armrests. Supporting structure in steel with top in conductive nylon. Black finish.
0830N	Height adjustable armrests. Supporting structure in reinforced nylon, shock-resistant and scratch-resistant, with top in soft polyurethane. Black finish.
M-0331	Conductive glides in black nylon (h 32 mm / Ø 50 mm). Instead of castors.

### TEST

UNI EN 1335-1+2+3
EN 100015-1
IEC 61340-5-1
D. Lgs. 81/2008 type B

Rev. 0	01-06-2018	ESD Professional: C-EX1111AS	Page 1 of 1
Rev. 1	01-01-2020	ESD Professional: C-EX1111AS	Page 1 of 1