


## Clean-Room ESD PU C-WG1862HAP / C-WG1872HAP

PRODUCT	DIMENSIONS	C-WG1862HAP	C-WG1872HAP
	Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	420 mm 390 mm 390 mm 260-330 mm 70 mm 430 mm 500-700 mm	420 mm 390 mm 390 mm 260-330 mm 70 mm 430 mm 600-850 mm

### TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of ultra-light integral polyurethane mixed with carbon fibers (PU-Touch ESD). Colour Anthracite GRY-ESD. Non-toxic material and without CFC/HCFC. ESD material conductivity of $10^7$ ohm.
Backrest	Internal structure in steel rods ( $\varnothing$ 10 mm), covered by a compound of ultra-light integral polyurethane mixed with carbon fibers (PU-Touch ESD). Colour Anthracite GRY-ESD. Non-toxic material and without CFC/HCFC. Outer shell in shaped metal, painted in black. ESD material conductivity of $10^7$ ohm.
Mechanism	<b>AS2:</b> A-SYNCHRON BI-LEVER, independent backrest inclination of $9^\circ$ positive and $16^\circ$ negative, seat of $6^\circ$ positive and $4^\circ$ negative, lockable in all positions. Push button activated backrest height adjustment. According to UNI EN 1335-3.
Lift action	Central piston ( $\varnothing$ 28 mm) protected by steel tube ( $\varnothing$ 50 mm), chrome finish. Class 4 according to DIN 4550.
Base	<b>0901C:</b> 5-star base ( $\varnothing$ 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Glides	<b>0331:</b> conductive glides in black nylon (h 32 mm / $\varnothing$ 50 mm).

### ACCESSORIES

M-0321	Conductive castors ( $\varnothing$ 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
0700ESD	Conductive circular footrest ( $\varnothing$ 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
NO-OIL	Gas lift with sealing ring for oil and grease.