


## Clean-Room ESD Stools/Standing-Aid C-KGT143HAS / C-KGT144HAS

PRODUCT	DIMENSIONS	C-KGT143HAS	C-KGT144HAS
	Seat diameter Seat height	390 mm 500-700 mm	390 mm 600-850 mm

### TECHNICAL DESCRIPTION

Seat	Internal structure in polyethylene anatomically shaped, with integrated reinforcement ribs.
Padding	PU-Flex, 20 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.
Upholstery	<b>ECR7</b> Composition: 90% PVC, 10% cotton/polyester Weight: 630 g/m <sup>2</sup> Colour fastness to light: UNI EN ISO 105-B02 Xenotest (Level 5) Colours: Black 1104
Mechanism	<b>GS:</b> GAS LIFT, seat height adjustable.
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), chrome finish. Class 4 according to DIN 4550.
Base	<b>0902C:</b> 5-star base (Ø 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Glides	<b>0331:</b> conductive glides in black nylon (h 32 mm / Ø 50 mm).

### ACCESSORIES

M-0321	Conductive castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
0700ESD	Conductive circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
NO-OIL	Gas lift with sealing ring for oil and grease.