


Production Standard P-VL1510F

PRODUCT		DIMENSIONS	P-VL1510F
		Seat depth from lumbar support	410-460 mm
		Seat depth	420 mm
		Seat width	430 mm
		Backrest height from seat	290-390 mm
		Backrest height adjustment	100 mm
		Backrest width	390 mm
		Seat height	400-530 mm
TECHNICAL DESCRIPTION			
Seat	Structure in multilayered beech wood anatomically shaped, 10 mm thickness, natural water based painted. Low formaldehyde emission according to class E1.		
Backrest	Structure in multilayered beech wood anatomically shaped, 11 mm thickness, natural water based painted. Low formaldehyde emission according to class E1.		
Mechanism	GS: GAS LIFT, seat height adjustable. Knob activated backrest height adjustment.		
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.		
Base	0902P: 5-star base (Ø 600 mm) in nylon and fiberglass compound with internal reinforcement ribs, steel ring embedded in the conical coupling. Black finish. According to ANSI/BIFMA X5.1 and UNI EN 1335-3.		
Castors	0302: hard castors (Ø 50 mm) in black nylon, self-braking.		
ACCESSORIES			
M-0311	Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of 0302 castors.		
M-0351	Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.		
0902C	5-star base (Ø 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish.		
0903COL	5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Varnished with RAL color on demand.		