


## Production Stools/Standing-Aid P-KG143H / P-KG144H

PRODUCT	DIMENSIONS	P-KG143H	P-KG144H
	Seat diameter Seat height	390 mm 490-690 mm	390 mm 590-840 mm

### TECHNICAL DESCRIPTION

Seat	Structure in polyethylene anatomically shaped, 40 mm thickness, with integrated reinforcement ribs. Colours: Dark grey DGY / Navy BLU / Beige SND
Mechanism	<b>GS:</b> GAS LIFT, seat height adjustable.
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.
Base	<b>0902P:</b> 5-star base (Ø 600 mm) in nylon and fiberglass compound with internal reinforcement ribs, steel ring embedded in the conical coupling. Black finish. According to ANSI/BIFMA X5.1 and UNI EN 1335-3.
Glides	<b>0351:</b> glides in black nylon (h 55 mm / Ø 50 mm).

### ACCESSORIES

M-0311	Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
M-0302	Hard castors (Ø 50 mm) in black nylon, self-braking. Instead of glides.
0700	Circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
0701	Circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable by pressure.
0902C	5-star base (Ø 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish.
0903COL	5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Varnished with RAL color on demand.