


## ESD Standard A-VL1461HAS / A-VL1471HAS

PRODUCT	DIMENSIONS	A-VL1461HAS	A-VL1471HAS
	Seat depth from lumbar support	440 mm	440 mm
	Seat depth	470 mm	470 mm
	Seat width	480 mm	480 mm
	Backrest height from seat	420-480 mm	420-480 mm
	Backrest height adjustment	60 mm	60 mm
	Backrest width	430 mm	430 mm
	Seat height	500-700 mm	600-850 mm

### TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm variable thickness. Low formaldehyde emission according to class E1. Outer shell in recyclable techno-polymer for internal components protection.
Backrest	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs. Outer shell in conductive recyclable techno-polymer for internal components protection.
Padding	Seat in PU-Flex, 40 mm thickness and 40 g/L density. Backrest in PU-Flex, 35 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.
Upholstery	<b>ESD2</b> Composition: 99% polypropylene, 1% carbon Weight: 320 g/lmt Abrasion: UNI EN ISO 12947 (>30.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, BS 5852 Crib 5, California TB 117 Colors: Anthracite 1601 / Black 1654
Mechanism	<b>PC: PERMANENT CONTACT</b> , backrest inclination of 20° lockable in all positions. Knob activated backrest height adjustment. According to UNI EN 1335-3.
Lift action	Central piston (∅ 28 mm) protected by steel tube (∅ 50 mm), chrome finish. Class 4 according to DIN 4550.
Base	<b>0901C</b> : 5-star base (∅ 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Glides	<b>0331</b> : conductive glides in black nylon (h 32 mm / ∅ 50 mm).

### ACCESSORIES

M-0321	Conductive castors (∅ 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
0700ESD	Conductive circular footrest (∅ 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.

### TEST

UNI EN 1335-1+2+3
EN 100015-1
IEC 61340-5-1
D. Lgs. 81/2008 type B