


## ESD Standard A-VL1463HAS

PRODUCT	DIMENSIONS	A-VL1463HAS	
	Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	440 mm 470 mm 480 mm 420-480 mm 60 mm 430 mm 520-720 mm	

### TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm variable thickness. Low formaldehyde emission according to class E1. Outer shell in recyclable techno-polymer for internal components protection.
Backrest	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs. Outer shell in conductive recyclable techno-polymer for internal components protection.
Padding	Seat in PU-Flex, 40 mm thickness and 40 g/L density. Backrest in PU-Flex, 35 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.
Upholstery	<b>ESD2</b> Composition: 99% polypropylene, 1% carbon Weight: 320 g/lmt Abrasion: UNI EN ISO 12947 (>30.000 Martindale cycles) Flammability: UNI 9175 (Class 11M), EN 1021-1+2, BS 5852 Crib 5, California TB 117 Colors: Anthracite 1601 / Black 1654
Mechanism	<b>AS3:</b> A-SYNCHRON TRI-LEVER, backrest inclination of 12° positive and 28° negative, additional tilting activation with consequent inclination of the seat of 5 ° positive and 3 ° negative, lockable in all positions. Knob activated backrest height adjustment. According to UNI EN 1335-3.
Lift action	Central piston (∅ 28 mm) protected by steel tube (∅ 50 mm), chrome finish. Class 4 according to DIN 4550.
Base	<b>0901C:</b> 5-star base (∅ 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Glides	<b>0331:</b> conductive glides in black nylon (h 32 mm / ∅ 50 mm).

### ACCESSORIES

M-0321	Conductive castors (∅ 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
0700ESD	Conductive circular footrest (∅ 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.

### TEST

UNI EN 1335-1+2+3
EN 100015-1
IEC 61340-5-1
D. Lgs. 81/2008 type B