


## ESD Standard A-VL1661HAS / A-VL1671HAS

PRODUCT		DIMENSIONS	A-VL1661HAS	A-VL1671HAS
		Seat depth from lumbar support	440 mm	440 mm
		Seat depth	470 mm	470 mm
		Seat width	480 mm	480 mm
		Backrest height from seat	530-590 mm	530-590 mm
		Backrest height adjustment	60 mm	60 mm
		Backrest width	430 mm	430 mm
		Seat height	500-700 mm	600-850 mm
TECHNICAL DESCRIPTION				
Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm variable thickness. Low formaldehyde emission according to class E1. Outer shell in recyclable techno-polymer for internal components protection.			
Backrest	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs. Outer shell in conductive recyclable techno-polymer for internal components protection.			
Padding	Seat in PU-Flex, 40 mm thickness and 40 g/L density. Backrest in PU-Flex, 35 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.			
Upholstery	<b>ESD2</b> Composition: 99% polypropylene, 1% carbon Weight: 320 g/lmt Abrasion: UNI EN ISO 12947 (>30.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, BS 5852 Crib 5, California TB 117 Colors: Anthracite 1601 / Black 1654  <b>ESD5</b> Composizione: 65% poliammide Cradura™, 14% lana vergine, 10% viscosa Red. Lenzing FR™, 8% poliestere, 3% fibre metalliche Peso: 437 g/mtl Abrasione: EN ISO 12947 (> 150.000 cicli Martindale) Infiammabilità: UNI 9175 (Classe 1IM), EN 1021-1+2, BS 5852-0+1Crib 5, California TB 117 Colori: Blu 1506 / Bordeaux 1501			
Mechanism	<b>PC: PERMANENT CONTACT</b> , backrest inclination of 20° lockable in all positions. Knob activated backrest height adjustment. According to UNI EN 1335-3.			
Lift action	Central piston (∅ 28 mm) protected by steel tube (∅ 50 mm), chrome finish. Class 4 according to DIN 4550.			
Base	<b>0901C</b> : 5-star base (∅ 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.			
Glides	<b>0331</b> : conductive glides in black nylon (h 32 mm / ∅ 50 mm).			

**ESD Standard**  
**A-VL1661HAS / A-VL1671HAS**

<b>ACCESSORIES</b>	
0860AN	Height adjustable conductive armrests. Supporting structure in steel with top in conductive nylon. Black finish.
0830N	Height adjustable armrests. Supporting structure in reinforced nylon, shock-resistant and scratch-resistant, with top in soft polyurethane. Black finish.
M-0321	Conductive castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
0700ESD	Conductive circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
<b>TEST</b>	
UNI EN 1335-1+2+3	
EN 100015-1	
IEC 61340-5-1	
D. Lgs. 81/2008 type B	