


ESD Stools/Standing-Aid A-WG141AP

PRODUCT	DIMENSIONS	A-WG141AP	
	Seat depth Seat width Seat height	390 mm 390 mm 410-540 mm	

TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of ultra-light integral polyurethane mixed with carbon fibers (PU-Touch ESD). Colour Anthracite GRY-ESD. Non-toxic material and without CFC/HCFC. ESD material conductivity of 10^7 ohm.
Mechanism	GS: GAS LIFT, seat height adjustable.
Lift action	Central piston (\varnothing 28 mm) protected by steel tube (\varnothing 50 mm), chrome finish. Class 4 according to DIN 4550.
Base	0902C: 5-star base (\varnothing 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Castors	0321: conductive castors (\varnothing 50 mm) in black nylon with non-marking polyurethane ring, self-braking.

ACCESSORIES

M-0331	Conductive glides in black nylon (h 32 mm / \varnothing 50 mm). Instead of castors.
--------	---------------------------------------------------------------------------------------

TEST

EN 100015-1
IEC 61340-5-1