


ESD PU Intense-Use A-WG1812AP

PRODUCT	DIMENSIONS	A-WG1812AP	
	Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	440 mm 390 mm 390 mm 260-330 mm 70 mm 430 mm 420-550 mm	

TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of ultra-light integral polyurethane mixed with carbon fibers (PU-Touch ESD). Colour Anthracite GRY-ESD. Non-toxic material and without CFC/HCFC. ESD material conductivity of 10 ⁷ ohm.
Backrest	Internal structure in steel rods (Ø 10 mm), covered by a compound of ultra-light integral polyurethane mixed with carbon fibers (PU-Touch ESD). Colour Anthracite GRY-ESD. Non-toxic material and without CFC/HCFC. Outer shell in shaped metal, painted in black. ESD material conductivity of 10 ⁷ ohm.
Mechanism	AS2: A-SYNCHRON BI-LEVER, independent backrest inclination of 9° positive and 16° negative, seat of 6° positive and 4° negative, lockable in all positions. Push button activated backrest height adjustment. According to UNI EN 1335-3.
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), chrome finish. Class 4 according to DIN 4550.
Base	0901C: 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Castors	0321: conductive castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking.

ACCESSORIES

M-0331	Conductive glides in black nylon (h 32 mm / Ø 50 mm). Instead of castors.
--------	---

TEST

EN 100015-1
 IEC 61340-5-1
 DIN 68877-1-2:2016
 DIN 1728:2014