


## ESD Stools/Standing-Aid A-WG143HAP / A-WG144HAP

PRODUCT	DIMENSIONS	A-WG143HAP	A-WG144HAP
	Seat depth Seat width Seat height	390 mm 390 mm 490-690 mm	390 mm 390 mm 590-840 mm

**TECHNICAL DESCRIPTION**

Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of ultra-light integral polyurethane mixed with carbon fibers (PU-Touch ESD). Colour Anthracite GRY-ESD. Non-toxic material and without CFC/HCFC. ESD material conductivity of $10^7$ ohm.
Mechanism	<b>GS:</b> GAS LIFT, seat height adjustable.
Lift action	Central piston ( $\varnothing$ 28 mm) protected by steel tube ( $\varnothing$ 50 mm), chrome finish. Class 4 according to DIN 4550.
Base	<b>0902C:</b> 5-star base ( $\varnothing$ 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Glides	<b>0331:</b> conductive glides in black nylon (h 32 mm / $\varnothing$ 50 mm).

**ACCESSORIES**

M-0321	Conductive castors ( $\varnothing$ 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
0700ESD	Conductive circular footrest ( $\varnothing$ 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.

**TEST**

 EN 100015-1  
 IEC 61340-5-1