


ESD PU A-WG1863HAP / A-WG1873HAP

PRODUCT	DIMENSIONS	A-WG1863HAP	A-WG1873HAP
	Seat depth from lumbar support	440 mm	440 mm
	Seat depth	390 mm	390 mm
	Seat width	390 mm	390 mm
	Backrest height from seat	140-380 mm	140-380 mm
	Backrest height adjustment	240 mm	240 mm
	Backrest width	430 mm	430 mm
	Seat height	500-700 mm	600-850 mm

TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of ultra-light integral polyurethane mixed with carbon fibers (PU-Touch ESD). Color Black BLK-ESD. Non-toxic material and without CFC/HCFC. ESD material conductivity of 10 ⁷ ohm.
Backrest	Internal structure in steel rods (Ø 10 mm), covered by a compound of ultra-light integral polyurethane mixed with carbon fibers (PU-Touch ESD). Color Black BLK-ESD. Non-toxic material and without CFC/HCFC. Outer shell in shaped metal, painted in black. ESD material conductivity of 10 ⁷ ohm.
Mechanism	AS3: A-SYNCHRON TRI-LEVER, backrest inclination of 12° positive and 28° negative, additional tilting activation with consequent inclination of the seat of 5 ° positive and 3 ° negative, lockable in all positions. Knob activated backrest height adjustment. According to UNI EN 1335-3.
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), chrome finish. Class 4 according to DIN 4550.
Base	0903C: 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Glides	0331: conductive glides in black nylon (h 32 mm / Ø 50 mm).

ACCESSORIES

M-0321	Conductive castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
0700ESD	Conductive circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.

TEST

EN 100015-1
IEC 61340-5-1
DIN 68877-1-2:2016
DIN 1728:2014