


ESD Stools/Standing-Aid A-KGT143HAS / A-KGT144HAS

PRODUCT		DIMENSIONS	A-KGT143HAS	A-KGT144HAS
		Seat diameter Seat height	390 mm 500-700 mm	390 mm 600-850 mm
TECHNICAL DESCRIPTION				
Seat	Internal structure in polyethylene anatomically shaped, with integrated reinforcement ribs.			
Padding	PU-Flex, 20 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.			
Upholstery	<p>ESD2 Composition: 99% polypropylene, 1% carbon Weight: 320 g/lmt Abrasion: UNI EN ISO 12947 (>30.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, BS 5852 Crib 5, California TB 117 Colors: Anthracite 1601 / Black 1654</p> <p>ESD5 Composition: 65% polyamide Cradura™, 14% virgin wool, 10% viscose Red. Lenzing FR™, 8% polyester, 3% metallic fibers Weight: 437 g/lmt Abrasion: EN ISO 12947 (> 150.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, BS 5852-0+1 Crib 5, California TB 117 Colors: Blue 1506 / Dark red 1501</p>			
Mechanism	GS: GAS LIFT, seat height adjustable.			
Lift action	Central piston (∅ 28 mm) protected by steel tube (∅ 50 mm), chrome finish. Class 4 according to DIN 4550.			
Base	0902C: 5-star base (∅ 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.			
Glides	0331: conductive glides in black nylon (h 32 mm / ∅ 50 mm).			
ACCESSORIES				
M-0321	Conductive castors (∅ 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.			
0700ESD	Conductive circular footrest (∅ 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.			
TEST				
EN 100015-1				
IEC 61340-5-1				