


ESD Professional A-LE1112AS

PRODUCT	DIMENSIONS	A-LE1112AS	
	Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	440 mm 440 mm 440 mm 510-580 mm 70 mm 470 mm 420-550 mm	
TECHNICAL DESCRIPTION			
Seat	Internal structure in multilayered beech wood anatomically shaped, 12 mm thickness. Low formaldehyde emission according to class E1. Wood FSC certified.		
Backrest	Internal structure in multilayered beech wood anatomically shaped, 12 mm thickness. Low formaldehyde emission according to class E1. Wood FSC certified.		
Padding	Seat in PU-Flex, 45 mm thickness and 40 g/L density. Backrest in PU-Flex, 35 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.		
Upholstery	ESD2 Composition: 99% polypropylene, 1% carbon Weight: 320 g/lmt Abrasion: UNI EN ISO 12947 (>30.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, BS 5852 Crib 5, California TB 117 Colors: Anthracite 1601 / Black 1654 ESD5 Composition: 65% polyamide Cradura™, 14% virgin wool, 10% viscose Red. Lenzing FR™, 8% polyester, 3% metallic fibers Weight: 437 g/lmt Abrasion: EN ISO 12947 (> 150.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, BS 5852-0+1 Crib 5, California TB 117 Colors: Blue 1506 / Dark red 1501		
Mechanism	AS2: A-SYNCHRON BI-LEVER, independent backrest inclination of 9° positive and 16° negative, seat of 6° positive and 4° negative, lockable in all positions. Push button activated backrest height adjustment (70 mm). According to UNI EN 1335-3.		
Lift action	Central piston (∅ 28 mm) protected by steel tube (∅ 50 mm), chrome finish. Class 4 according to DIN 4550.		
Base	0901C: 5-star base (∅ 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.		
Castors	0321: conductive castors (∅ 50 mm) in black nylon with non-marking polyurethane ring, self-braking.		

ESD Professional
A-LE1112AS**ACCESSORIES**

0860AN	Height adjustable conductive armrests. Supporting structure in steel with top in conductive nylon. Black finish.
0830N	Height adjustable armrests. Supporting structure in reinforced nylon, shock-resistant and scratch-resistant, with top in soft polyurethane. Black finish.
M-0331	Conductive glides in black nylon (h 32 mm / Ø 50 mm). Instead of castors.

TEST

EN 100015-1
IEC 61340-5-1
UNI EN 1335-1+2
D. Lgs. 81/2008 type B
UNI EN1022:2018
UNI EN 1728:2012+AC:2013