


## ESD Professional A-LE1667HAS / A-LE1677HAS

PRODUCT		DIMENSIONS	A-LE1667HAS	A-LE1677HAS
		Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	420-490 mm 440 mm 440 mm 470-540 mm 70 mm 470 mm 520-720 mm	420-490 mm 440 mm 440 mm 470-540 mm 70 mm 470 mm 620-870 mm
TECHNICAL DESCRIPTION				
Seat	Internal structure in multilayered beech wood anatomically shaped, 11 mm thickness. Low formaldehyde emission according to class E1. Wood FSC certified.			
Backrest	Internal structure in multilayered beech wood anatomically shaped, 12 mm thickness. Low formaldehyde emission according to class E1. Wood FSC certified.			
Padding	Seat in PU-Flex, 45 mm thickness and 40 g/L density. Backrest in PU-Flex, 35 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.			
Upholstery	<b>ESD2</b> Composition: 99% polypropylene, 1% carbon Weight: 320 g/lmt Abrasion: UNI EN ISO 12947 (>30.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, BS 5852 Crib 5, California TB 117 Colors: Anthracite 1601 / Black 1654  <b>ESD5</b> Composition: 65% polyamide Cradura™, 14% virgin wool, 10% viscose Red. Lenzing FR™, 8% polyester, 3% metallic fibers Weight: 437 g/lmt Abrasion: EN ISO 12947 (> 150.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, BS 5852-0+1 Crib 5, California TB 117 Colors: Blue 1506 / Dark red 1501			
Mechanism	<b>TS: TENSION SOFT</b> , synchronized backrest inclination of 21° and seat of 10° lockable in 6 positions, antishock system and quick release (7 steps) side tension adjustment control. Additional negative inclination of -5° for the backrest and -2° for the seat. Seat depth adjustment, run 70 mm. Push button system for backrest height adjustment (60 mm), lockable in 13 positions. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.			

## ESD Professional A-LE1667HAS / A-LE1677HAS

Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), chrome finish. Class 4 according to DIN 4550.
Base	<b>0901C</b> : 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Glides	<b>0331</b> : conductive glides in black nylon (h 32 mm / Ø 50 mm).
<b>ACCESSORIES</b>	
0860AN	Height adjustable conductive armrests. Supporting structure in steel with top in conductive nylon. Black finish.
0830N	Height adjustable armrests. Supporting structure in reinforced nylon, shock-resistant and scratch-resistant, with top in soft polyurethane. Black finish.
M-0321	Conductive castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
0700ESD	Conductive circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.

### TEST

EN 100015-1  
 IEC 61340-5-1  
 UNI EN 1335-1+2  
 D. Lgs. 81/2008 type B  
 UNI EN1022:2018  
 UNI EN 1728:2012+AC:2013