

## Clean-Room Standard C-VL1115S

PRODUCT	DIMENSIONS	C-VL1115S
	Seat depth from lumbar support	440 mm
	Seat depth	470 mm
	Seat width	480 mm
	Backrest height from seat	530-590 mm
	Backrest height adjustment	60 mm
	Backrest width	430 mm
	Seat height	440-570 mm
TECHNICAL DESCRIPTION		
Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm variable thickness. Low formaldehyde emission according to class E1. Outer shell in recyclable techno-polymer for internal components protection.	
Backrest	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs. Outer shell in recyclable techno-polymer for internal components protection.	
Padding	Seat in PU-Flex, 40 mm thickness and 40 g/L density. Backrest in PU-Flex, 35 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.	
Upholstery	<b>VALENCIA (ANTIBACTERIAL)</b> Composition: outside 100% PVC, inside 100% polyester Hi-Loft2™ Weight: 890 g/lmt Abrasion: DIN EN ISO 12947-2 (> 300.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, DIN 4102 (B2), ÖNORM B3825 (B1), ÖNORM A3800-1 (Q1) Bacterial resistance according to AATCC TM147 Resistant to disinfectants, blood and urine Colors: Throna color chart <b>TOLEDO</b> Composition: 84% PVC, 16% polyester Weight: 1.036 g/lmt Abrasion: DIN EN ISO 5470-2 (> 100.000 Martindale cycles) Flammability: DIN EN 1021-1+2, BS 5852-0+1Crib 5, MVSS302 Resistant to disinfectants, blood and urine. Colors: Black 014	
Mechanism	<b>SS: SYNCHRON SOFT</b> , synchronized backrest inclination of 20° and seat of 8° lockable in 4 positions, antishock system and tension adjustment control by means of a knob placed on the right side of the seat. Backrest and seat tilt lock/unlock using a rotary knob located on the left side of the seat. Seat height adjustment using a lever located on the right side of the seat. Up-down system for backrest height adjustment, lockable in 7 positions. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.	
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.	
Base	<b>0901C</b> : 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.	
Castors	<b>0311</b> : Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking.	

## Clean-Room Standard C-VL1115S

### ACCESSORIES

M-0351	Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.
0860N	Height adjustable armrests. Supporting structure in steel with top in nylon. Black finish.
NO-OIL	Gas lift with sealing ring for oil and grease.

### TEST

UNI EN 1335-1+2+3  
D. Lgs. 81/2008 type A