


Clean-Room Standard C-VL1661HS / C-VL1771HS

PRODUCT	DIMENSIONS	C-VL1661HS	C-VL1671HS
	Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	440 mm 470 mm 480 mm 530-590 mm 60 mm 430 mm 500-700 mm	440 mm 470 mm 480 mm 530-590 mm 60 mm 430 mm 600-850 mm
TECHNICAL DESCRIPTION			
Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm variable thickness. Low formaldehyde emission according to class E1. Outer shell in recyclable techno-polymer for internal components protection.		
Backrest	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs. Outer shell in recyclable techno-polymer for internal components protection.		
Padding	Seat in PU-Flex, 40 mm thickness and 40 g/L density. Backrest in PU-Flex, 35 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.		
Upholstery	VALENCIA (ANTIBACTERIAL) Composition: outside 100% PVC, inside 100% polyester Hi-Loft2™ Weight: 890 g/lmt Abrasion: DIN EN ISO 12947-2 (> 300.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, DIN 4102 (B2), ÖNORM B3825 (B1), ÖNORM A3800-1 (Q1) Bacterial resistance according to AATCC TM147 Resistant to disinfectants, blood and urine Colors: Throna color chart TOLEDO Composition: 84% PVC, 16% polyester Weight: 1.036 g/lmt Abrasion: DIN EN ISO 5470-2 (> 100.000 Martindale cycles) Flammability: DIN EN 1021-1+2, BS 5852-0+1Crib 5, MVSS302 Resistant to disinfectants, blood and urine. Colors: Black 014		
Mechanism	PC: PERMANENT CONTACT , backrest inclination of 20° lockable in all positions. Knob activated backrest height adjustment. According to UNI EN 1335-3.		
Lift action	Central piston (∅ 28 mm) protected by steel tube (∅ 50 mm), black finish. Class 4 according to DIN 4550.		
Base	0901C : 5-star base (∅ 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.		
Glides	0351 : glides in black nylon (h 55 mm / ∅ 50 mm).		

Clean-Room Standard
C-VL1661HS / C-VL1671HS

ACCESSORIES	
M-0311	Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
M-0302	Hard castors (Ø 50 mm) in black nylon, self-braking. Instead of glides.
0860N	Height adjustable armrests. Supporting structure in steel with top in nylon. Black finish.
0700	Circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
NO-OIL	Gas lift with sealing ring for oil and grease.
TEST	
UNI EN 1335-1+2+3	
D. Lgs. 81/2008 type B	