


## Clean-Room PU Intense-Use C-WG1862HP / C-WG1872HP

PRODUCT	DIMENSIONS	C-WG1862HP	C-WG1872HP
	Seat depth from lumbar support	420 mm	420 mm
	Seat depth	390 mm	390 mm
	Seat width	390 mm	390 mm
	Backrest height from seat	260-330 mm	260-330 mm
	Backrest height adjustment	70 mm	70 mm
	Backrest width	430 mm	430 mm
	Seat height	500-700 mm	600-850 mm

### TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of ultra-light integral polyurethane (PU-Touch). Colour Anthracite GRY. Non-toxic material and without CFC/HCFC.
Backrest	Internal structure in steel rods (Ø 10 mm), covered by a compound of ultra-light integral polyurethane (PU-Touch). Colour Anthracite GRY. Non-toxic material and without CFC/HCFC. Outer shell in shaped metal, painted in black.
Mechanism	<b>AS2:</b> A-SYNCHRON BI-LEVER, independent backrest inclination of 9° positive and 16° negative, seat of 6° positive and 4° negative, lockable in all positions. Push button activated backrest height adjustment. According to UNI EN 1335-3.
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.
Base	<b>0901C:</b> 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Glides	<b>0351:</b> glides in black nylon (h 55 mm / Ø 50 mm).

### ACCESSORIES

M-0311	Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
M-0302	Hard castors (Ø 50 mm) in black nylon, self-braking. Instead of glides.
0700	Circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
NO-OIL	Gas lift with sealing ring for oil and grease.

### TEST

PTP 177.0/20 Measurement of antibacterial activity on surfaces  
 DIN 68877-1-2:2016