


Clean-Room PU Intense-Use C-WG1814P

PRODUCT	DIMENSIONS	C-WG1814P	
	Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	400 mm 390 mm 390 mm 290-350 mm 60 mm 430 mm 420-550 mm	

TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of ultra-light integral polyurethane (PU-Touch). Colour Anthracite GRY. Non-toxic material and without CFC/HCFC.
Backrest	Internal structure in steel rods (Ø 10 mm), covered by a compound of ultra-light integral polyurethane (PU-Touch). Colour Anthracite GRY. Non-toxic material and without CFC/HCFC. Outer shell in shaped metal, painted in black.
Mechanism	PCP: PERMANENT CONTACT PLUS, backrest inclination of 20° lockable in 4 positions, antishock system and tension adjustment control. Push button activated backrest height adjustment. According to UNI EN 1335-3
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.
Base	0901C: 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Castors	0311: Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking.

ACCESSORIES

M-0351	Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.
NO-OIL	Gas lift with sealing ring for oil and grease.

TEST

PTP 177.0/20 Measurement of antibacterial activity on surfaces
 DIN 68877-1-2:2016