

Clean-Room Standard C-FC1010

PRODUCT	DIMENSIONS	C-FC1010
---------	------------	----------



Seat depth from lumbar support	440 mm
Backrest height from seat	430 mm
Seat depth	450 mm
Seat width	460 mm
Backrest height	320 mm
Backrest width	420 mm
Seat height	390-520 mm

TECHNICAL DESCRIPTION

Seat	Structure of the seat in black polypropylene (PP), anatomically shaped and with reinforcing ribs. BLK: Black (standard) GRY: Grey RAL7040 / BLU: Blue RAL5002 / RED: Red (optional instead of black color)
Backrest	Structure of the backrest in black polypropylene (PP), anatomically shaped and with reinforcing ribs. BLK: Black (standard) GRY: Grey RAL7040 / BLU: Blue RAL5002 / RED: Red (optional instead of black color)
Back support	Supporting structure black color, in polyamide (PA) and fiberglass (PA 6 GF40), with reinforcing ribs.
Mechanism	GS: GAS LIFT, seat height adjustable.
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.
Base	0901C: 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Castors	0311: Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking.

ACCESSORIES

FC-01	Upholstered seat panel. Padding in PU-Flex, 10 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC. Upholstery in eco-leather: VALENCIA. Composition: outside 100% PVC, inside 100% polyester Hi-Loft2™ TOLEDO. Composition: 84% PVC, 16% polyester
FC-STR-GRY	Supporting structure in Grey color. Instead of black color structure.
M-0351	Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.
0703N	"T" shaped black nylon armrests.
NO-OIL	Gas lift with sealing ring for oil and grease.

TEST

ISO 22196:2011 Measurement of antibacterial activity on plastic and other non-porous surfaces