


Clean-Room HEPA C-HP1012S

PRODUCT	DIMENSIONS	C-HP1012S
	Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	380 mm 450 mm 450 mm 410-480 mm 70 mm 410 mm 440-570 mm
TECHNICAL DESCRIPTION		
Seat	Internal structure in multilayered beech wood anatomically shaped, 11 mm thickness. Low formaldehyde emission according to class E1. Wood FSC certified. Hermetic PVC profile seal. HEPA 200 P2P EN 143:00 filter for dust particles.	
Backrest	Internal structure in multilayered beech wood anatomically shaped, 12 mm thickness. Low formaldehyde emission according to class E1. Wood FSC certified. Hermetic PVC profile seal.	
Padding	Seat in PU-Flex, 40 mm thickness and 40 g/L density. Backrest in PU-Flex, 40 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.	
Upholstery	VALENCIA (ANTIBACTERIAL) Composition: outside 100% PVC, inside 100% polyester Hi-Loft2™ Weight: 890 g/lmt Abrasion: DIN EN ISO 12947-2 (> 300.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, DIN 4102 (B2), ÖNORM B3825 (B1), ÖNORM A3800-1 (Q1) Bacterial resistance according to AATCC TM147 Resistant to disinfectants, blood and urine Colors: Throna color chart TOLEDO Composition: 84% PVC, 16% polyester Weight: 1.036 g/lmt Abrasion: DIN EN ISO 5470-2 (> 100.000 Martindale cycles) Flammability: DIN EN 1021-1+2, BS 5852-0+1Crib 5, MVSS302 Resistant to disinfectants, blood and urine. Colors: Black 014	
Mechanism	AS2: A-SYNCHRON BI-LEVER, independent backrest inclination of 9° positive and 16° negative, seat of 6° positive and 4° negative, lockable in all positions. Push button activated backrest height adjustment. According to UNI EN 1335-3.	
Lift action	NO-OIL: Central piston (∅ 28 mm) protected by steel tube (∅ 50 mm), black finish, with sealing ring for oil and grease retention. Class 4 according to DIN 4550.	
Base	0907C: 5-star base (∅ 700 mm) in die-cast aluminum with internal reinforcement ribs, anti-slip tips. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.	
Castors	0311: Soft castors (∅ 50 mm) in black nylon with non-marking polyurethane ring, self-braking.	
ACCESSORIES		
M-0351	Glides in black nylon (h 55 mm / ∅ 50 mm). Instead of castors.	
TEST		