


## Clean-Room Stools/Standing-Aid C-KGT141

PRODUCT	DIMENSIONS	C-KGT141	
	Seat diameter Seat height	390 mm 420-550 mm	
TECHNICAL DESCRIPTION			
Seat	Internal structure in polyethylene anatomically shaped, with integrated reinforcement ribs.		
Padding	PU-Flex, 20 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.		
Upholstery	<b>VALENCIA (ANTIBACTERIAL)</b> Composition: outside 100% PVC, inside 100% polyester Hi-Loft2™ Weight: 890 g/lmt Abrasion: DIN EN ISO 12947-2 (> 300.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, DIN 4102 (B2), ÖNORM B3825 (B1), ÖNORM A3800-1 (Q1) Bacterial resistance according to AATCC TM147 Resistant to disinfectants, blood and urine Colors: Throna color chart <b>TOLEDO</b> Composition: 84% PVC, 16% polyester Weight: 1.036 g/lmt Abrasion: DIN EN ISO 5470-2 (> 100.000 Martindale cycles) Flammability: DIN EN 1021-1+2, BS 5852-0+1Crib 5, MVSS302 Resistant to disinfectants, blood and urine. Colors: Black 014		
Mechanism	<b>GS:</b> GAS LIFT, seat height adjustable.		
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.		
Base	<b>0902C:</b> 5-star base (Ø 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.		
Castors	<b>0311:</b> Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking.		
ACCESSORIES			
M-0351	Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.		
NO-OIL	Gas lift with sealing ring for oil and grease.		