

## **DATASHEET**

UNI EN ISO 9001:2015 UNI EN ISO 14001:2015 UNI ISO 45001:2018

## Clean-Room PU C-TL1811P

PRODUCT		DIMENSIONS	C-TL1811P			
		Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	410 mm 430 mm 470 mm 420-450 mm 30 mm 420 mm 410-540 mm			
TECHNICAL DESCRIPTION						
Seat	Internal structure in multilayered beech wood anatomically shaped, 11 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of soft integral polyurethane (PU-Soft). Colour Black BLK. Non-toxic material and without CFC/HCFC.					
Backrest	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs, covered by a compound of soft integral polyurethane (PU-Soft). Colour Black BLK. Non-toxic material and without CFC/HCFC.					
Mechanism	<b>PC:</b> PERMANENT CONTACT, backrest inclination of 20° lockable in all positions. Knob activated backrest height adjustment. According to UNI EN 1335-3.					
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.					
Base	<b>0901C</b> : 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.					
Castors	<b>0311:</b> Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking.					
ACCESSORIES						
M-0351	Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.					
NO-OIL	Gas lift with sealing ring for oil and grease.					
TEST						
PTP 177.0/20 Measurement of antibacterial activity on surfaces						
ANSI/BIFMA X5	•					
EN1335/2-00 Pa						
EN1335/3-00 Pa	ar. 5/6.1/6.2/7					

Rev. 1	01-01-2020	Clean-Room PU: C-TL1811P	Page 1 of 1