


Clean-Room PU Intense-Use C-TL1862HP / C-TL1872HP

| PRODUCT | DIMENSIONS | C-TL1862HP | C-TL1872HP |
|---|--|---|---|
|  | Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height | 380 mm 430 mm 470 mm 350-420 mm 70 mm 420 mm 510-710 mm | 380 mm 430 mm 470 mm 350-420 mm 70 mm 420 mm 610-860 mm |

TECHNICAL DESCRIPTION

| | |
|-------------|--|
| Seat | Internal structure in multilayered beech wood anatomically shaped, 11 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of soft integral polyurethane (PU-Soft). Colour Black BLK. Non-toxic material and without CFC/HCFC. |
| Backrest | Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs, covered by a compound of soft integral polyurethane (PU-Soft). Colour Black BLK. Non-toxic material and without CFC/HCFC. |
| Mechanism | AS2: A-SYNCHRON BI-LEVER, independent backrest inclination of 9° positive and 16° negative, seat of 6° positive and 4° negative, lockable in all positions. Push button activated backrest height adjustment. According to UNI EN 1335-3. |
| Lift action | Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550. |
| Base | 0901C: 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3. |
| Glides | 0351: glides in black nylon (h 55 mm / Ø 50 mm). |

ACCESSORIES

| | |
|--------|---|
| M-0311 | Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides. |
| M-0302 | Hard castors (Ø 50 mm) in black nylon, self-braking. Instead of glides. |
| 0700 | Circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob. |
| NO-OIL | Gas lift with sealing ring for oil and grease. |

TEST

| |
|--|
| PTP 177.0/20 Measurement of antibacterial activity on surfaces |
| ANSI/BIFMA X5.1-2002/8-11 |
| EN1335/2-00 Par. 5 |
| EN1335/3-00 Par. 5/6.1/6.2/7 |