


## Clean-Room PU C-TL1813P

PRODUCT	DIMENSIONS	C-TL1813P	
	Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	410 mm 430 mm 470 mm 350-420 mm 70 mm 420 mm 430-560 mm	

### TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 11 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of soft integral polyurethane (PU-Soft). Colour Black BLK. Non-toxic material and without CFC/HCFC.
Backrest	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs, covered by a compound of soft integral polyurethane (PU-Soft). Colour Black BLK. Non-toxic material and without CFC/HCFC.
Mechanism	<b>AS3:</b> A-SYNCHRON TRI-LEVER, backrest inclination of 12° positive and 28° negative, seat of 5° positive and 3° negative, lockable in all positions. With combined activation of tilting mechanism and backrest inclination. Knob activated backrest height adjustment. According to UNI EN 1335-3.
Lift action	Central piston (∅ 28 mm) protected by steel tube (∅ 50 mm), black finish. Class 4 according to DIN 4550.
Base	<b>0901C:</b> 5-star base (∅ 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Castors	<b>0311:</b> Soft castors (∅ 50 mm) in black nylon with non-marking polyurethane ring, self-braking.

### ACCESSORIES

M-0351	Glides in black nylon (h 55 mm / ∅ 50 mm). Instead of castors.
NO-OIL	Gas lift with sealing ring for oil and grease.

### TEST

PTP 177.0/20 Measurement of antibacterial activity on surfaces

ANSI/BIFMA X5.1-2002/8-11

EN1335/2-00 Par. 5

EN1335/3-00 Par. 5/6.1/6.2/7