


Clean-Room Standard C-VL1011S

PRODUCT	DIMENSIONS	C-VL1011S
	Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	440 mm 470 mm 480 mm 420-480 mm 60 mm 430 mm 420-550 mm
TECHNICAL DESCRIPTION		
Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm variable thickness. Low formaldehyde emission according to class E1. Outer shell in recyclable techno-polymer for internal components protection.	
Backrest	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs. Outer shell in recyclable techno-polymer for internal components protection.	
Padding	Seat in PU-Flex, 40 mm thickness and 40 g/L density. Backrest in PU-Flex, 35 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.	
Upholstery	VALENCIA (ANTIBACTERIAL) Composition: outside 100% PVC, inside 100% polyester Hi-Loft2™ Weight: 890 g/lmt Abrasion: DIN EN ISO 12947-2 (> 300.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, DIN 4102 (B2), ÖNORM B3825 (B1), ÖNORM A3800-1 (Q1) Bacterial resistance according to AATCC TM147 Resistant to disinfectants, blood and urine Colors: Throna color chart TOLEDO Composition: 84% PVC, 16% polyester Weight: 1.036 g/lmt Abrasion: DIN EN ISO 5470-2 (> 100.000 Martindale cycles) Flammability: DIN EN 1021-1+2, BS 5852-0+1Crib 5, MVSS302 Resistant to disinfectants, blood and urine. Colors: Black 014	
Mechanism	PC: PERMANENT CONTACT , backrest inclination of 20° lockable in all positions. Knob activated backrest height adjustment. According to UNI EN 1335-3.	
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.	
Base	0901C: 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.	
Castors	0311: Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking.	

Clean-Room Standard C-VL1011S

ACCESSORIES

M-0351	Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.
0860N	Height adjustable armrests. Supporting structure in steel with top in nylon. Black finish.
NO-OIL	Gas lift with sealing ring for oil and grease.

TEST

UNI EN 1335-1+2+3
D. Lgs. 81/2008 type B