


Clean-Room PU C-TL1863HP

PRODUCT	DIMENSIONS	C-TL1863HP
	Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	410 mm 430 mm 470 mm 350-420 mm 70 mm 420 mm 510-710 mm

TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 11 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of soft integral polyurethane (PU-Soft). Colour Black BLK. Non-toxic material and without CFC/HCFC.
Backrest	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs, covered by a compound of soft integral polyurethane (PU-Soft). Colour Black BLK. Non-toxic material and without CFC/HCFC.
Mechanism	AS3: A-SYNCHRON TRI-LEVER, backrest inclination of 12° positive and 28° negative, seat of 5° positive and 3° negative, lockable in all positions. With combined activation of tilting mechanism and backrest inclination. Knob activated backrest height adjustment. According to UNI EN 1335-3.
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.
Base	0901C: 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Glides	0351: glides in black nylon (h 55 mm / Ø 50 mm).

ACCESSORIES

M-0311	Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
M-0302	Hard castors (Ø 50 mm) in black nylon, self-braking. Instead of glides.
0700	Circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
NO-OIL	Gas lift with sealing ring for oil and grease.

TEST

PTP 177.0/20 Measurement of antibacterial activity on surfaces
ANSI/BIFMA X5.1-2002/8-11
EN1335/2-00 Par. 5
EN1335/3-00 Par. 5/6.1/6.2/7