


OTC O-VL1011S

PRODUCT	DIMENSIONS	O-VL1011S	
	Seat depth from lumbar support	440 mm	
	Seat depth	470 mm	
	Seat width	480 mm	
	Backrest height from seat	420-480 mm	
	Backrest height adjustment	60 mm	
	Backrest width	430 mm	
	Seat height	420-550 mm	

TECHNICAL DESCRIPTION

Seat	<p>Internal structure in multilayered beech wood anatomically shaped, 11 mm variable thickness. Low formaldehyde emission according to class E1. Outer shell in recyclable techno-polymer for internal components protection.</p>
Backrest	<p>Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs. Outer shell in recyclable techno-polymer for internal components protection.</p>
Padding	<p>Seat in PU-Flex, 40 mm thickness and 40 g/L density. Backrest in PU-Flex, 35 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.</p>
Upholstery	<p>MIRAGE (ANTIBACTERIAL) Composition: 100% polyester FR Weight: 460 g/lmt Abrasion: UNI EN ISO 12947 (> 100.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, DIN 4102 (B1), BS 5852 Crib 5, ÖNORM B3825 (B1), ÖNORM 3800-1 (Q1), FR - M1, NF D 60-013 (AM18), California TB 117 Antibacterial activity test method AATCC 100:2012, ASTM E2149-13a Colors: Black 724 / Dark grey 739 / Dark blue 734 / Red 721</p> <p>PLANET Composition: 87,5% PVC, 12,5% cotton Weight: 900 g/lmt Abrasion: ISO 5470-2 (>200.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1, BS 5852-1 Crib 5 Colors: Black 114</p> <p>BLOOM Composition: 85% PVC, 15% polyester Weight: 550 g/m² Abrasion: UNI EN ISO 12947-2 (> 50.000 Martindale cycles) Colours: Black 124 / Grey 127 / Royal blue 126 / Red 121</p>
Upholstery	<p>VALENCIA (ANTIBACTERIAL) Composition: outside 100% PVC, inside 100% polyester Hi-Loft2™ Weight: 890 g/lmt Abrasion: DIN EN ISO 12947-2 (> 300.000 Martindale cycles) Flammability: UNI 9175 (Cl 1IM), EN 1021-1+2, DIN 4102 (B2), ÖNORM B3825 (B1), A3800-1 (Q1) Bacterial resistance according to AATCC TM147 Resistant to disinfectants, blood and urine Colors: Throna color chart</p>

OTC O-VL1011S

Mechanism	PC: PERMANENT CONTACT, backrest inclination of 20° lockable in all positions. Knob activated backrest height adjustment. According to UNI EN 1335-3.
Lift action	Central piston (∅ 28 mm) protected by steel tube (∅ 50 mm), black finish. Class 4 according to DIN 4550.
Base	0902P: 5-star base (∅ 600 mm) in nylon and fiberglass compound with internal reinforcement ribs, steel ring embedded in the conical coupling. Black finish. According to ANSI/BIFMA X5.1 and UNI EN 1335-3.
Castors	0302: hard castors (∅ 50 mm) in black nylon, self-braking.
ACCESSORIES	
M-0311	Soft castors (∅ 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of 0302 castors.
M-0351	Glides in black nylon (h 55 mm / ∅ 50 mm). Instead of castors.
0902C	5-star base (∅ 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish.