


## 24-Hour Basic K08

PRODUCT	DIMENSIONS	K08	
	Seat depth from lumbar support	410-470 mm	
	Seat depth	480 mm	
	Seat width	510 mm	
	Backrest height from seat	600 mm	
	Lumbar support run	50 mm	
	Backrest width	480 mm	
	Width between armrests	510 mm	
	Seat height	440-550 mm	
TECHNICAL DESCRIPTION			
Seat	Internal structure in polypropylene (PPK20) deriving from recycled and recyclable material, anatomically shaped with special reinforcement ribs and iron reinforcement bars. Shockproof casing in recyclable polypropylene (PP) techno polymer to protect the internal mechanics.		
Backrest	Internal structure in recyclable polypropylene (PPK20), anatomically shape with reinforcement ribs. Shockproof casing in recyclable polypropylene (PP) techno polymer to protect the internal mechanics.		
Lumbar	Integrated lumbar support, height adjustable (50 mm) by means of an easily operated push button located on the back of the backrest.		
Padding	Seat in PU-Flex, 50 mm thickness and 60 g/L density. Extra wadding 20 mm thickness. Backrest in PU-Flex, 35 mm thickness and 60 g/L density. Extra wadding 20 mm thickness. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.		
Upholstery	<p><b>H24/250</b> Composition: 62% polyamide Cradura™, 14% virgin wool, 10% viscose Red. Lenzing FR™, 11% Polyester, 3% metallic fibers Weight: 450 g/lmt Abrasion: ISO 12947-2 (&gt; 500.000 Martindale cycles) Flammability: EN 1021-1+2 (M2), BS 5852-0+1, California TB 117 Color: Black 024 / Grey 027 / Navy 026 / Red 021 The fabric has a non-slip effect ideal for intensive use. The fabric is optimized to resist to velcro straps. Depending on the season, it gives the feeling of a pleasant warmth or freshness.</p> <p><b>MIRAGE (ANTIBACTERIAL)</b> Composition: 100% polyester FR Weight: 460 g/lmt Abrasion: UNI EN ISO 12947 (&gt; 100.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, DIN 4102 (B1), BS 5852 Crib 5, ÖNORM B3825 (B1), ÖNORM 3800-1 (Q1), FR - M1, NF D 60-013 (AM18), California TB 117 Antibacterial activity test method AATCC 100:2012, ASTM E2149-13a Colors: Black 724 / Dark grey 739 / Dark blue 734 / Red 721</p> <p><b>TOLEDO</b> Composition: 84% PVC, 16% polyester Weight: 1.036 g/lmt Abrasion: DIN EN ISO 5470-2 (&gt; 100.000 Martindale cycles) Flammability: DIN EN 1021-1+2, BS 5852-0+1Crib 5, MVSS302 Resistant to disinfectants, blood and urine. Colors: Black 014</p>		

## 24-Hour Basic K08

Armrests	<b>0840N</b> : 3D armrests adjustable in height, depth and rotation. Supporting structure in nylon with top in black soft polyurethane.
Mechanism	<b>TS</b> : TENSION SOFT, synchronized backrest inclination of 21° and seat of 10° lockable in 6 positions, antishock system and quick release (7 steps) side tension adjustment control. Additional negative inclination of -5° for the backrest and -2° for the seat. Seat depth adjustment, run 60 mm. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Lift	Weights up to 180 kg.
Lift action	Central piston (∅ 28 mm) protected by steel tube (∅ 50 mm), chrome finish. Class 4 according to DIN 4550.
Base	<b>0907C</b> : 5-star base (∅ 700 mm) in die-cast aluminum with internal reinforcement ribs, anti-slip tips. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Castors	<b>0360</b> : soft castors (∅ 60 mm) in black nylon with non-marking polyurethane ring, self-braking.

### ACCESSORI

0840C	4D armrests adjustable in height, width, depth and rotation. Supporting structure in polished aluminum with top in black soft polyurethane.
-------	---

### TEST

Certification phase:    BS 5459-2:2000+A2:2008 P. A.5.1/2/3/4/5  
                                   BS 5459-2:2000+A2:2008 P. A.6  
                                   BS5459-2:2000+A2:2008 P. A.7.2/3/4/5/6/8/9  
                                   BS5459-2:2000+A2:2008 DECLARATION OF CONFORMITY

UNI EN 1335-1+2

UNI EN 1728:2012

UNI EN 1022-2018

D. Lgs. 81/2008 tipo B

ANSI-BIFMA X5.1-2017/15-14-9-10-11-5-12-13-8-20-7-16-21-6