


24-Hour Basic K06HS / K07HS

PRODUCT	DIMENSIONS	K06HS	K07HS
	Seat depth from lumbar support	380 mm	380 mm
	Seat depth	450 mm	450 mm
	Seat width	450 mm	450 mm
	Backrest height from seat	410-480 mm	410-480 mm
	Backrest height adjustment	70 mm	70 mm
	Backrest width	410 mm	410 mm
	Seat height	500-700 mm	600-850 mm

TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 11 mm thickness. Low formaldehyde emission according to class E1. Wood FSC certified. All around soft rubber (PVC) profile for impact protection.
Backrest	Internal structure in multilayered beech wood anatomically shaped, 12 mm thickness. Low formaldehyde emission according to class E1. Wood FSC certified. All around soft rubber (PVC) profile for impact protection.
Padding	Seat in PU-Flex, 50 mm thickness and 40 g/L density. Backrest in PU-Flex, 40 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.
Upholstery	<p>H24/250 Composition: 62% polyamide Cradura™, 14% virgin wool, 10% viscose Red. Lenzing FR™, 11% Polyester, 3% metallic fibers Weight: 450 g/lmt Abrasion: ISO 12947-2 (> 500.000 Martindale cycles) Flammability: EN 1021-1+2 (M2), BS 5852-0+1, California TB 117 Color: Black 024 / Grey 027 / Navy 026 / Red 021 The fabric has a non-slip effect ideal for intensive use. The fabric is optimized to resist to velcro straps. Depending on the season, it gives the feeling of a pleasant warmth or freshness.</p> <p>MIRAGE (ANTIBACTERIAL) Composition: 100% polyester FR Weight: 460 g/lmt Abrasion: UNI EN ISO 12947 (> 100.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, DIN 4102 (B1), BS 5852 Crib 5, ÖNORM B3825 (B1), ÖNORM 3800-1 (Q1), FR - M1, NF D 60-013 (AM18), California TB 117 Antibacterial activity test method AATCC 100:2012, ASTM E2149-13a Colors: Black 724 / Dark grey 739 / Dark blue 734 / Red 721</p> <p>TOLEDO Composition: 84% PVC, 16% polyester Weight: 1.036 g/lmt Abrasion: DIN EN ISO 5470-2 (> 100.000 Martindale cycles) Flammability: DIN EN 1021-1+2, BS 5852-0+1Crib 5, MVSS302 Resistant to disinfectants, blood and urine. Colors: Black 014</p>

24-Hour Basic K06HS / K07HS

Mechanism	AS2: A-SYNCHRON BI-LEVER, independent backrest inclination of 9° positive and 16° negative, seat of 6° positive and 4° negative, lockable in all positions. Push button activated backrest height adjustment 70 mm. According to UNI EN 1335-3.
Lift	Weights up to 150 kg
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.
Base	0907C: 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs, anti-slip tips. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Glides	0351: glides in black nylon (h 55 mm / Ø 50 mm).
ACCESSORIES	
0840C	4D armrests adjustable in height, width, depth and rotation. Supporting structure in polished aluminum with top in black soft polyurethane.
0830N	Height adjustable armrests. Supporting structure in reinforced nylon, shock-resistant and scratch-resistant, with top in soft polyurethane. Black finish.
M-0360	Soft castors (Ø 60 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
0700	Circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
0731	Circular ootrest (Ø 600 mm) with black metal board, black varnished ring and supports, height adjustable with a knob.
TEST	