


ESD Professional A-EX1661HAS / A-EX1671HAS

PRODUCT		DIMENSIONS	A-EX1661HAS	A-EX1671HAS
		Seat depth from lumbar support	440 mm	440 mm
		Seat depth	470 mm	470 mm
		Seat width	510 mm	510 mm
		Backrest height from seat	530-590 mm	530-590 mm
		Backrest height adjustment	60 mm	60 mm
		Backrest width	470 mm	470 mm
		Seat height	500-700 mm	600-850 mm
		TECHNICAL DESCRIPTION		
Seat	<p>Internal structure in multilayered beech wood anatomically shaped, 10 mm variable thickness. Low formaldehyde emission according to class E1. Outer shell in recyclable techno-polymer for internal components protection. Additional shell in recyclable techno-polymer for mechanism total encasement and protection.</p>			
Backrest	<p>Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs. Outer shell in conductive recyclable techno-polymer for internal components protection.</p>			
Padding	<p>Seat in PU-Flex, 45 mm thickness and 40 g/L density. Backrest in PU-Flex, 35 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.</p>			
Upholstery	<p>ESD2 Composition: 99% polypropylene, 1% carbon Weight: 320 g/lmt Abrasion: UNI EN ISO 12947 (>30.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, BS 5852 Crib 5, California TB 117 Colors: Anthracite 1601 / Black 1654</p> <p>ESD5 Composition: 65% polyamide Cradura™, 14% virgin wool, 10% viscose Red. Lenzing FR™, 8% polyester, 3% metallic fibers Weight: 437 g/lmt Abrasion: EN ISO 12947 (> 150.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, BS 5852-0+1 Crib 5, California TB 117 Colors: Blue 1506 / Dark red 1501</p>			
Mechanism	<p>PCX: PERMANENT CONTACT X, backrest inclination of 25°, lockable in all positions, with antishock. Up&Down activated backrest height adjustment, lockable in 7 positions. According to UNI EN 1335-3.</p>			
Lift action	<p>Central piston (∅ 28 mm) protected by steel tube (∅ 50 mm), chrome finish. Class 4 according to DIN 4550.</p>			
Base	<p>0901C: 5-star base (∅ 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.</p>			
Glides	<p>0331: conductive glides in black nylon (h 32 mm / ∅ 50 mm).</p>			

ESD Professional
A-EX1661HAS / A-EX1671HAS

ACCESSORIES	
0860AN	Height adjustable conductive armrests. Supporting structure in steel with top in conductive nylon. Black finish.
0830N	Height adjustable armrests. Supporting structure in reinforced nylon, shock-resistant and scratch-resistant, with top in soft polyurethane. Black finish.
M-0321	Conductive castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
0700ESD	Conductive circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
TEST	
UNI EN 1335-1+2+3	
EN 100015-1	
IEC 61340-5-1	
D. Lgs. 81/2008 type B	