


## Laboratory Tech L-VL1564HF / L-VL1574HF

PRODUCT	DIMENSIONS	L-VL1564HF	L-VL1574HF
	Seat depth from lumbar support Backrest height from seat Backrest height adjustment Seat depth Seat width Backrest width Seat height	410 mm 300-370 mm 70 mm 420 mm 430 mm 390 mm 500-700 mm	410 mm 300-370 mm 70 mm 420 mm 430 mm 390 mm 600-850 mm

### TECHNICAL DESCRIPTION

Seat	Structure in multilayered beech wood anatomically shaped, 10 mm thickness, natural water based painted. Low formaldehyde emission according to class E1.
Backrest	Structure in multilayered beech wood anatomically shaped, 11 mm thickness, natural water based painted. Low formaldehyde emission according to class E1.
Mechanism	<b>PCP:</b> PERMANENT CONTACT PLUS, backrest inclination of 20° lockable in 4 positions, antishock system and tension adjustment control. Push button activated backrest height adjustment. According to UNI EN 1335-3.
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.
Base	<b>0902P:</b> 5-star base (Ø 600 mm) in nylon and fiberglass compound with internal reinforcement ribs, steel ring embedded in the conical coupling. Black finish. According to ANSI/BIFMA X5.1 and UNI EN 1335-3.
Glides	<b>0351:</b> glides in black nylon (h 55 mm / Ø 50 mm).

### ACCESSORIES

M-0311	Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
M-0302	Hard castors (Ø 50 mm) in black nylon, self-braking. Instead of glides.
0700	Circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
0902C	5-star base (Ø 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish.