


Clean-Room HEPA C-HE1013S

PRODUCT		DIMENSIONS	C-HE1013S
		Seat depth from lumbar support	420 mm
		Seat depth	430 mm
		Seat width	440 mm
		Backrest height from seat	390-500 mm
		Backrest height adjustment	110 mm
		Backrest width	410 mm
		Seat height	440-570 mm
		TECHNICAL DESCRIPTION	
Seat	Internal structure in multilayered beech wood anatomically shaped, 11 mm thickness. Low formaldehyde emission according to class E1. Wood FSC certified. Hermetic PVC profile seal. HEPA 200 P2P EN 143:00 filter for dust particles.		
Backrest	Internal structure in multilayered beech wood anatomically shaped, 12 mm thickness. Low formaldehyde emission according to class E1. Wood FSC certified. Hermetic PVC profile seal.		
Padding	Seat in PU-Flex, 40 mm thickness and 40 g/L density. Backrest in PU-Flex, 40 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.		
Upholstery	<p>VALENCIA (ANTIBACTERIAL) Composition: outside 100% PVC, inside 100% polyester Hi-Loft2™ Weight: 890 g/lmt Abrasion: DIN EN ISO 12947-2 (> 300.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, DIN 4102 (B2), ÖNORM B3825 (B1), ÖNORM A3800-1 (Q1) Bacterial resistance according to AATCC TM147 Resistant to disinfectants, blood and urine Colors: Throna color chart</p> <p>TOLEDO Composition: 84% PVC, 16% polyester Weight: 1.036 g/lmt Abrasion: DIN EN ISO 5470-2 (> 100.000 Martindale cycles) Flammability: DIN EN 1021-1+2, BS 5852-0+1Crib 5, MVSS302 Resistant to disinfectants, blood and urine. Colors: Black 014</p>		
Mechanism	AS3: A-SYNCHRON TRI-LEVER, backrest inclination of 12° positive and 28° negative, seat of 5° positive and 3° negative, lockable in all positions. With combined activation of tilting mechanism and backrest inclination. Knob activated backrest height adjustment. According to UNI EN 1335-3.		
Lift action	NO-OIL: Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish, with sealing ring for oil and grease retention. Class 4 according to DIN 4550.		
Base	0907C: 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs, anti-slip tips. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.		
Castors	0311: Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking.		
ACCESSORIES			
M-0351	Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.		
TEST			