


## Clean-Room PU C-TL1861HP / C-TL1871HP

PRODUCT	DIMENSIONS	C-TL1861HP	C-TL1871HP
	Seat depth from lumbar support	410 mm	410 mm
	Seat depth	430 mm	430 mm
	Seat width	470 mm	470 mm
	Backrest height from seat	420-450 mm	420-450 mm
	Backrest height adjustment	30 mm	30 mm
	Backrest width	420 mm	420 mm
	Seat height	490-690 mm	590-840 mm

### TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 11 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of soft integral polyurethane (PU-Soft). Colour Black BLK. Non-toxic material and without CFC/HCFC.
Backrest	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs, covered by a compound of soft integral polyurethane (PU-Soft). Colour Black BLK. Non-toxic material and without CFC/HCFC.
Mechanism	<b>PC: PERMANENT CONTACT</b> , backrest inclination of 20° lockable in all positions. Knob activated backrest height adjustment. According to UNI EN 1335-3.
Lift action	Central piston (∅ 28 mm) protected by steel tube (∅ 50 mm), black finish. Class 4 according to DIN 4550.
Base	<b>0901C</b> : 5-star base (∅ 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Glides	<b>0351</b> : glides in black nylon (h 55 mm / ∅ 50 mm).

### ACCESSORIES

M-0311	Soft castors (∅ 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
M-0302	Hard castors (∅ 50 mm) in black nylon, self-braking. Instead of glides.
0700	Circular footrest (∅ 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
NO-OIL	Gas lift with sealing ring for oil and grease.

### TEST

PTP 177.0/20 Measurement of antibacterial activity on surfaces
ANSI/BIFMA X5.1-2002/8-11
EN1335/2-00 Par. 5
EN1335/3-00 Par. 5/6.1/6.2/7