


Clean-Room PU Intense-Use C-TL1812P

PRODUCT	DIMENSIONS	C-TL1812P	
	Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	380 mm 430 mm 470 mm 350-420 mm 70 mm 420 mm 430-560 mm	

TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 11 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of soft integral polyurethane (PU-Soft). Colour Black BLK. Non-toxic material and without CFC/HCFC.
Backrest	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs, covered by a compound of soft integral polyurethane (PU-Soft). Colour Black BLK. Non-toxic material and without CFC/HCFC.
Mechanism	AS2: A-SYNCHRON BI-LEVER, independent backrest inclination of 9° positive and 16° negative, seat of 6° positive and 4° negative, lockable in all positions. Push button activated backrest height adjustment. According to UNI EN 1335-3.
Lift action	Central piston (∅ 28 mm) protected by steel tube (∅ 50 mm), black finish. Class 4 according to DIN 4550.
Base	0901C: 5-star base (∅ 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Castors	0311: Soft castors (∅ 50 mm) in black nylon with non-marking polyurethane ring, self-braking.

ACCESSORIES

M-0351	Glides in black nylon (h 55 mm / ∅ 50 mm). Instead of castors.
NO-OIL	Gas lift with sealing ring for oil and grease.

TEST

PTP 177.0/20 Measurement of antibacterial activity on surfaces
ANSI/BIFMA X5.1-2002/8-11
EN1335/2-00 Par. 5
EN1335/3-00 Par. 5/6.1/6.2/7