


Clean-Room ESD PU C-WG1863HAP / C-WG1873HAP

PRODUCT		DIMENSIONS	C-WG1863HAP	C-WG1873HAP
		Seat depth from lumbar support	440 mm	440 mm
		Seat depth	390 mm	390 mm
		Seat width	390 mm	390 mm
		Backrest height from seat	140-380 mm	140-380 mm
		Backrest height adjustment	240 mm	240 mm
		Backrest width	430 mm	430 mm
		Seat height	500-700 mm	600-850 mm
TECHNICAL DESCRIPTION				
Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of ultra-light integral polyurethane mixed with carbon fibers (PU-Touch ESD). Colour Anthracite GRY-ESD. Non-toxic material and without CFC/HCFC. ESD material conductivity of 10 ⁷ ohm.			
Backrest	Internal structure in steel rods (Ø 10 mm), covered by a compound of ultra-light integral polyurethane mixed with carbon fibers (PU-Touch ESD). Colour Anthracite GRY-ESD. Non-toxic material and without CFC/HCFC. Outer shell in shaped metal, painted in black. ESD material conductivity of 10 ⁷ ohm.			
Mechanism	AS3: A-SYNCHRON TRI-LEVER, backrest inclination of 12° positive and 28° negative, seat of 5° positive and 3° negative, lockable in all positions. With combined activation of tilting mechanism and backrest inclination. Knob activated backrest height adjustment. According to UNI EN 1335-3.			
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), chrome finish. Class 4 according to DIN 4550.			
Base	0901C: 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.			
Glides	0331: conductive glides in black nylon (h 32 mm / Ø 50 mm).			
ACCESSORIES				
M-0321	Conductive castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.			
0700ESD	Conductive circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.			
NO-OIL	Gas lift with sealing ring for oil and grease.			