


## Clean-Room ESD PU Intense-Use C-TL1862HAP / C-TL1872HAP

PRODUCT	DIMENSIONS	C-TL1862HAP	C-TL1872HAP
	Seat depth from lumbar support	380 mm	380 mm
	Seat depth	430 mm	430 mm
	Seat width	470 mm	470 mm
	Backrest height from seat	350-420 mm	350-420 mm
	Backrest height adjustment	70 mm	70 mm
	Backrest width	420 mm	420 mm
	Seat height	510-710 mm	610-860 mm

### TECHNICAL DESCRIPTION

Seat	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs and steel bars, covered by a compound of soft integral polyurethane mixed with carbon fibers (PU-Soft ESD). Colour Black BLK-ESD. Non-toxic and without CFC/HCFC. ESD material conductivity of 10 <sup>7</sup> ohm.
Backrest	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs and steel bars, covered by a compound of soft integral polyurethane mixed with carbon fibers (PU-Soft ESD). Colour Black BLK-ESD. Non-toxic and without CFC/HCFC. ESD material conductivity of 10 <sup>7</sup> ohm.
Mechanism	<b>AS2:</b> A-SYNCHRON BI-LEVER, independent backrest inclination of 9° positive and 16° negative, seat of 6° positive and 4° negative, lockable in all positions. Push button activated backrest height adjustment. According to UNI EN 1335-3.
Lift action	Central piston (∅ 28 mm) protected by steel tube (∅ 50 mm), chrome finish. Class 4 according to DIN 4550.
Base	<b>0901C:</b> 5-star base (∅ 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Glides	<b>0331:</b> conductive glides in black nylon (h 32 mm / ∅ 50 mm).

### ACCESSORIES

M-0321	Conductive castors (∅ 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
0860AN	Height adjustable conductive armrests. Supporting structure in steel with top in conductive nylon. Black finish.
0700ESD	Conductive circular footrest (∅ 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
NO-OIL	Gas lift with sealing ring for oil and grease.

### TEST

UNI EN 1335-2+3
EN 100015-1
IEC 61340-5-1