


Clean-Room ESD PU Intense-Use C-WG1814AP

PRODUCT		DIMENSIONS	C-WG1814AP
		Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	400 mm 390 mm 390 mm 290-350 mm 60 mm 430 mm 420-550 mm
TECHNICAL DESCRIPTION			
Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of ultra-light integral polyurethane mixed with carbon fibers (PU-Touch ESD). Colour Anthracite GRY-ESD. Non-toxic material and without CFC/HCFC. ESD material conductivity of 10 ⁷ ohm.		
Backrest	Internal structure in steel rods (Ø 10 mm), covered by a compound of ultra-light integral polyurethane mixed with carbon fibers (PU-Touch ESD). Colour Anthracite GRY-ESD. Non-toxic material and without CFC/HCFC. Outer shell in shaped metal, painted in black. ESD material conductivity of 10 ⁷ ohm.		
Mechanism	PCP: PERMANENT CONTACT PLUS , backrest inclination of 20° lockable in 4 positions, antishock system and tension adjustment control. Push button activated backrest height adjustment. According to UNI EN 1335-3.		
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), chrome finish. Class 4 according to DIN 4550.		
Base	0901C : 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.		
Castors	0321 : conductive castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking.		
ACCESSORIES			
M-0331	Conductive glides in black nylon (h 32 mm / Ø 50 mm). Instead of castors.		
NO-OIL	Gas lift with sealing ring for oil and grease.		