


Production Professional P-LE1667HS / P-1677HS

PRODUCT		DIMENSIONS	P-LE1667HS	P-LE1677HS
		Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	420-480 mm 440 mm 440 mm 470-540 mm 70 mm 470 mm 520-720 mm	420-480 mm 440 mm 440 mm 470-540 mm 70 mm 470 mm 620-870 mm
TECHNICAL DESCRIPTION				
Seat	Internal structure in multilayered beech wood anatomically shaped, 11 mm thickness. Low formaldehyde emission according to class E1. Wood FSC certified.			
Backrest	Internal structure in multilayered beech wood anatomically shaped, 12 mm thickness. Low formaldehyde emission according to class E1. Wood FSC certified.			
Padding	Seat in PU-Flex, 45 mm thickness and 40 g/L density. Backrest in PU-Flex, 35 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.			
Upholstery	MIRAGE (ANTIBACTERIAL) Composition: 100% polyester FR Weight: 460 g/lmt Abrasion: UNI EN ISO 12947 (> 100.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, DIN 4102 (B1), BS 5852 Crib 5, ÖNORM B3825 (B1), ÖNORM 3800-1 (Q1), FR - M1, NF D 60-013 (AM18), California TB 117 Antibacterial activity test method AATCC 100:2012, ASTM E2149-13a Colours: Throna colour chart PLANET Composition: 87,5% PVC, 12,5% cotton Weight: 900 g/lmt Abrasion: ISO 5470-2 (>200.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1, BS 5852-1 Crib 5 Colors: Black 114			
Mechanism	TS: TENSION SOFT , synchronized backrest inclination of 21° and seat of 10° lockable in 6 positions, antishock system and quick release (7 steps) side tension adjustment control. Additional negative inclination of -5° for the backrest and -2° for the seat. Seat depth adjustment, run 50 mm. Push button system for backrest height adjustment (60 mm), lockable in 13 positions. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.			
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.			
Base	0902P: 5-star base (Ø 600 mm) in nylon and fiberglass compound with internal reinforcement ribs, steel ring embedded in the conical coupling. Black finish. According to ANSI/BIFMA X5.1 and UNI EN 1335-3.			
Glides	0351: glides in black nylon (h 55 mm / Ø 50 mm).			

Production Professional P-LE1667HS / P-1677HS

ACCESSORIES	
M-0311	Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of 0302 castors.
M-0351	Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.
M-0902C	5-star base (Ø 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish.
M-0903COL	5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Varnished with RAL color on demand.
M-0910V	5-star raised base (Ø 500 mm) in grey epoxy painted steel with rubber end-plugs.
0700	Circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
0731	Circular footrest (Ø 600 mm), black steel ring, supports in black painted steel, two metal boards, height adjustable with a knob.
TEST	