


Production PU P-WG1860HP / P-WG1870HP

PRODUCT	DIMENSIONS	P-WG1860HP	P-WG1870HP
	Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	380 mm 390 mm 390 mm 340-410 mm 70 mm 430 mm 480-680 mm	380 mm 390 mm 390 mm 340-410 mm 70 mm 430 mm 580-830 mm

TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of ultra-light integral polyurethane (PU-Touch). Colour Anthracite GRY. Non-toxic material and without CFC/HCFC.
Backrest	Internal structure in steel rods (\varnothing 10 mm), covered by a compound of ultra-light integral polyurethane (PU-Touch). Colour Anthracite GRY. Non-toxic material and without CFC/HCFC. Outer shell in shaped metal, painted in black.
Mechanism	GS: GAS LIFT, seat height adjustable. Knob activated backrest height adjustment.
Lift action	Central piston (\varnothing 28 mm) protected by steel tube (\varnothing 50 mm), black finish. Class 4 according to DIN 4550.
Base	0902P: 5-star base (\varnothing 600 mm) in nylon and fiberglass compound with internal reinforcement ribs, steel ring embedded in the conical coupling. Black finish. According to ANSI/BIFMA X5.1 and UNI EN 1335-3.
Glides	0351: glides in black nylon (h 55 mm / \varnothing 50 mm).

ACCESSORIES

M-0311	Soft castors (\varnothing 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
M-0302	Hard castors (\varnothing 50 mm) in black nylon, self-braking. Instead of glides.
M-0902C	5-star base (\varnothing 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish.
M-0903COL	5-star base (\varnothing 700 mm) in die-cast aluminum with internal reinforcement ribs. Varnished with RAL color on demand
M-0901V	5-star raised base (\varnothing 500 mm) in grey epoxy painted steel with rubber end-plugs.
0700	Circular footrest (\varnothing 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
0731	Circular footrest (\varnothing 600 mm), black steel ring, supports in black painted steel, two metal boards, height adjustable with a knob.

TEST

PTP 177.0/20 Measurement of antibacterial activity on surfaces
DIN 68877-1-2:2016