


Education Stools E-KGT143H / E-KGT144H

| PRODUCT | DIMENSIONS | E-KGT143H | E-KGT144H |
|---|------------------------------|----------------------|----------------------|
|  | Seat diameter Seat height | 390 mm 500-700 mm | 390 mm 600-850 mm |

TECHNICAL DESCRIPTION

| | |
|-------------|---|
| Seat | Internal structure in polyethylene anatomically shaped, with integrated reinforcement ribs. |
| Padding | PU-Flex, 20 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC. |
| Upholstery | MIRAGE MIRAGE (ANTIBACTERIAL) Composition: 100% polyester FR Weight: 460 g/lmt Abrasion: UNI EN ISO 12947 (> 100.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, DIN 4102 (B1), BS 5852 Crib 5, ÖNORM B3825 (B1), ÖNORM 3800-1 (Q1), FR - M1, NF D 60-013 (AM18), California TB 117 Antibacterial activity test method AATCC 100:2012, ASTM E2149-13a Colors: Black 724 / Dark grey 739 / Dark blue 734 / Red 721 PLANET Composition: 87,5% PVC, 12,5% cotton Weight: 900 g/lmt Abrasion: ISO 5470-2 (>200.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1, BS 5852-1 Crib 5 Colors: Black 114 |
| Mechanism | GS: GAS LIFT, seat height adjustable. |
| Lift action | Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550. |
| Base | 0902P: 5-star base (Ø 600 mm) in nylon and fiberglass compound with internal reinforcement ribs, steel ring embedded in the conical coupling. Black finish. According to ANSI/BIFMA X5.1 and UNI EN 1335-3. |
| Glides | 0351: glides in black nylon (h 55 mm / Ø 50 mm). |

ACCESSORIES

| | |
|--------|---|
| M-0311 | Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides. |
| M-0302 | Hard castors (Ø 50 mm) in black nylon, self-braking. Instead of glides. |
| 0700 | Circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob. |
| 0902C | 5-star base (Ø 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. |